Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2014

Supplier's name or trade mark: HISENSE

Supplier's address: Partizanska 12, 3320 Velenje, SI

Model identifier: WDQA8014EVJM

General	product	parameters:
idellelai	DIOUULL	parameters.

General product parameters:						
Parameter	Value		Parameter	Value		
Rated capacity (kg)	Rated capacity	5,0		Height	85	
	Rated	8.0	Dimensions in cm	Width	60	
	washing capacity	8,0		Depth	54	
Energy Efficiency Index	EEI _w	51,6	Enorgy officionay class	EEI _w	Α	
	EEI _{wd}	67,0	Energy efficiency class	EEI _{wd}	D	
Washing efficiency index	I _w	1,031	Rinsing effectiveness (g/kg dry textile)	I _R	4,50	
	J _w	1,073		J _R	4,1	
Energy consumption in kWh per kg per cycle, for the washing cycle of the household washerdryer, using the eco 40-60 programme at a combination of full and partial loads. Actual energy consumption will depend on how the appliance is used		0,47	Energy consumption in kWh per kg per cycle, for the wash and dry cycle of the household washerdryer at a combination of full and half loads. Actual energy consumption will depend on how the appliance is used		2,66	
Water consumption in litre per cycle, for the eco 40-60 programme at a combination of full and partial loads. Actual water consumption will depend on how the appliance is used and on the hardness of the water		42	Water consumption in litre per cycle, for the wash and dry cycle of the household washerdryer at a combination of full and half loads. Actual water consumption will depend on how the appliance is used and on the hardness of the water		80	
Maximum temperature inside the treated textile (°C)	Rated washing capacity	34	Weighted remaining moisture			
	Half	30	content (%)	53	53,0	
	Quarter	25				
Spin speed (rpm)	Rated washing capacity	1400	Chin drying officional class	В		
	Half	1400	Spin-drying efficiency class			
	Quarter	1400				
Eco 40-60 programme duration (h:min)	Rated washing capacity	3:26	wash and dry cycle duration (h:min)	Rated capacity	11:30	
	Half	2:48		Half	8:00	
	Quarter	2:48				
Airborne acoustical noise emissions during the spinning phase for the eco 40-60 washing cycle at rated washing capacity (dB(A) re 1 pW)	74		Airborne acoustical noise emission class for the spinning phase for the eco 40-60 programme at rated washing capacity	D.		
Туре	Free-standing					
Off-mode (W)	0,49		Standby mode (W)		-	
Delay start (W)	3,70		Networked standby (W) -			
Minimum duration of the guarant	ee offered by	the manufa	acturer: 24 months			

No

This product has been designed to release silver ions during the washing cycle

Additional information:

http://global.hisense.com/